



Horizontal air discharge




With plenum box



With damper blade




With connecting frame



With butterfly damper

Ceiling diffusers

Type ADLQ



For four-way horizontal supply air discharge, with fixed air control blades – aluminium diffuser face

Square ceiling diffusers

- Nominal sizes 250, 300, 400, 500, 600, 625
- Volume flow rate range 20 – 665 l/s or 72 – 2394 m³/h
- Square diffuser face
- Diffuser face made of aluminium with anodised finish
- For supply and extract air
- For variable and constant volume flows
- For all types of ceiling systems
- High induction results in a rapid reduction of the temperature difference and airflow velocity

Optional equipment and accessories

- Exposed diffuser face available in RAL CLASSIC colours
- Horizontal or vertical duct connection
- Blanking plates for adjusting the discharge direction
- Duct cross bar for installation without plenum box
- Plenum box with cord-operated damper blade and pressure tap

Type		Page
ADLQ	General information	ADLQ – 2
	Function	ADLQ – 3
	Technical data	ADLQ – 4
	Quick sizing	ADLQ – 5
	Specification text	ADLQ – 7
	Order code	ADLQ – 8
	Variants	ADLQ – 9
	Dimensions and weight	ADLQ – 11
	Product details	ADLQ – 14
	Installation examples	ADLQ – 15
	Installation details	ADLQ – 16
	Commissioning	ADLQ – 18
	Basic information and nomenclature	ADLQ – 20

Application

Application

- Type ADLQ ceiling diffusers are used as supply air or extract air diffusers for comfort zones
- Attractive design element for building owners and architects with demanding aesthetic requirements
- Horizontal four-way supply air discharge for mixed flow ventilation
- High induction results in a rapid reduction of the temperature difference and airflow velocity (supply air variant)
- For variable and constant volume flows
- For supply air to room air temperature differences from –10 to +10 K
- For room heights up to 4 m (lower edge of suspended ceiling)
- For all types of ceiling systems

Special characteristics

- Horizontal four-way supply air discharge
- Diffuser face made of aluminium
- For all types of ceiling systems
- Horizontal or vertical duct connection

Nominal sizes

- 250, 300, 400, 500, 600, 625

Description

Variant

- Square diffuser face

Connection

- A: Diffuser face only
- AR: Vertical duct connection, with connecting frame
- AG: Vertical duct connection, with blades
- C: Vertical duct connection with butterfly damper
- AK: Horizontal duct connection, with plenum box

Parts and characteristics

- Square diffuser face with fixed air control blades
- Diffuser front frame
- Simple installation of the diffuser face due to central fixing screw with decorative cap

Accessories

- Lip seal

Construction features

- Spigot suitable for circular ducts to EN 1506 or EN 13180

Materials and surfaces

- Diffuser face made of extruded aluminium sections
- AK: Plenum box and cross bar made of galvanised sheet steel
- X: Plenum box made of plastic and galvanised sheet steel
- Connecting frame and butterfly damper made of sheet steel
- Lip seal made of rubber
- Attachments are dip coated RAL 9005, jet black
- Diffuser face with anodised finish, E6-C-0, natural colour
- P1: Powder-coated, RAL CLASSIC colour

Standards and guidelines

- Sound power level of the air-regenerated noise measured according to EN ISO 5135

Maintenance

- Maintenance-free as construction and materials are not subject to wear
- Inspection and cleaning to VDI 6022


Functional description

Ceiling diffusers direct the air from air conditioning systems into the room. The resulting airflow induces high levels of room air, thereby rapidly reducing the airflow velocity and the temperature difference between supply air and room air. Ceiling diffusers allow for large volume flow rates. The result is a mixed flow ventilation in comfort zones, with good overall room ventilation, creating

only very little turbulence in the occupied zone. Type ADLQ ceiling diffusers have fixed blades. Horizontal air discharge is four-way. The supply air to room air temperature difference may range from -10 to $+10$ K.


To give rooms an aesthetic, uniform look, Type ADLQ diffusers may also be used for extract air.

Schematic illustration of the ADLQ, with plenum box for horizontal duct connection



Air patterns

Horizontal air discharge



Nominal sizes	250, 300, 400, 500, 600, 625 mm
Minimum volume flow rate	20 – 250 l/s or 72 – 900 m³/h
Maximum volume flow rate, with $L_{WA} \cong 50$ dB(A)	575 – 665 l/s or 2070 – 2394 m³/h
Supply air to room air temperature difference	–10 to +10 K

This specification text describes the general properties of the product. Texts for variants can be generated with our Easy Product Finder design programme.

Ceiling diffusers with square diffuser face. Supply air and extract air variants for comfort zones. Diffuser face with fixed air control blades for horizontal four-way air discharge. For installation into all types of suspended ceilings. Ready-to-install component which consists of the aluminium diffuser face with fixed air control blades, a diffuser front frame with perimeter seal and a connecting frame, opposed action blades, butterfly damper or a plenum box. Diffuser face suitable for central screw fixing. Sound power level of the air-regenerated noise measured according to EN ISO 5135.

Special characteristics

- Horizontal four-way supply air discharge
- Diffuser face made of aluminium
- For all types of ceiling systems
- Horizontal or vertical duct connection

Materials and surfaces

- Diffuser face made of extruded aluminium sections
- AK: Plenum box and cross bar made of galvanised sheet steel
- X: Plenum box made of plastic and galvanised sheet steel
- Connecting frame and butterfly damper made

- of sheet steel
- Lip seal made of rubber
- Attachments are dip coated RAL 9005, jet black
- Diffuser face with anodised finish, E6-C-0, natural colour
- P1: Powder-coated, RAL CLASSIC colour


Technical data

- Nominal sizes: 250, 300, 400, 500, 600, 625 mm
- Minimum volume flow rate: 20 – 250 l/s or 72 – 900 m³/h
- Maximum volume flow rate, with $L_{WA} \approx 50$ dB(A): 575 – 665 l/s or 2070 – 2394 m³/h
- Supply air to room air temperature difference: –10 to +10 K


Sizing data

- $\dot{V}$ _____
[m³/h]
- Δp_t _____
[Pa]
- Air-regenerated noise
- L_{WA} _____
[dB(A)]


ADLQ/250




ADLQ/300




ADLQ/400




ADLQ/500



ADLQ/600



ADLQ/625



ADLQ-A

Variant

- Ceiling diffuser with square diffuser face

Nominal sizes

- 250, 300, 400, 500, 600, 625

Parts and characteristics

- Square diffuser face
- Simple installation of the diffuser face due to central fixing screw with decorative cap

ADLQ-AR

Variant

- Ceiling diffuser with square diffuser face
- With connecting frame

Nominal sizes

- 250, 300, 400, 500, 600, 625

Parts and characteristics

- Square diffuser face
- Connecting frame for installation of the diffuser into vertical ducts
- Simple installation of the diffuser face due to central fixing screw with decorative cap

ADLQ-C

Variant

- Ceiling diffuser with square diffuser face
- With connecting frame
- With butterfly damper

Nominal sizes

- 250, 300, 400, 500, 600, 625

Parts and characteristics

- Square diffuser face
- Connecting frame for installation of the diffuser into vertical ducts
- Butterfly damper for volume flow rate balancing
- Simple installation of the diffuser face due to central fixing screw with decorative cap

ADLQ-AG

Variant

- Ceiling diffuser with square diffuser face
- With connecting frame
- With opposed action blades

Nominal sizes

- 250, 300, 400, 500, 600, 625

Parts and characteristics

- Square diffuser face with fixed air control blades
- Diffuser front frame
- Simple installation of the diffuser face due to central fixing screw with decorative cap
- Connecting frame for installation of the diffuser into vertical ducts
- Damper blade for volume flow rate balancing

ADLQ-AK

Variant

- Ceiling diffuser with square diffuser face
- With plenum box for horizontal duct connection

Nominal sizes

- 250, 300, 400, 500, 600, 625

Parts and characteristics

- Square diffuser face
- Plenum box for horizontal duct connection
- Square opening to accommodate the diffuser face
- Equalising element that ensures a uniform


airflow through the diffuser face (supply air variant)

- Simple installation of the diffuser face due to central fixing screw with decorative cap
- Damper blade for volume flow rate balancing (optional)
- Pressure tap and cord-operated damper blade for volume flow rate balancing (optional)
- Lip seal (optional)

Construction features

- Spigot suitable for circular ducts to EN 1506 or EN 13180


ADLQ-A



ADLQ-A

Nominal size	□Q mm	□Q ₁ mm	H ₁ mm	H ₂ mm	m kg
250	140	248	13	29	0.5
300	190	298	13	29	0.7
400	290	398	13	29	1.3
500	390	498	13	29	1.8
600	490	598	13	29	2.5
625	515	623	13	29	2.6


ADLQ-AR



ADLQ-AR

Nominal size	□Q mm	□Q ₁ mm	H ₁ mm	H ₂ mm	m kg
250	143	248	13	52	0.7
300	193	298	13	52	1.0
400	293	398	13	52	1.7
500	393	498	13	52	2.3
600	493	598	13	52	3.0
625	518	623	13	52	3.2


ADLQ-C



ADLQ-C

Nominal size	□Q mm	□Q₁ mm	H₁ mm	H₂ mm	m kg
250	143	248	13	52	1.2
300	193	298	13	52	1.7
400	293	398	13	52	2.9
500	393	498	13	52	4.2
600	493	598	13	52	5.9
625	518	623	13	52	6.3


ADLQ-AG



ADLQ-AG

Nominal size	□Q mm	□Q₁ mm	H₁ mm	H₂ mm	m kg
250	143	248	13	95	0.9
300	193	298	13	95	1.4
400	293	398	13	95	2.5
500	393	498	13	95	3.6
600	493	598	13	95	5.0
625	518	623	13	95	5.6

Square diffuser face with plenum box for horizontal duct connection




ADLQ-AK

Nominal size	$\square Q_1$	H_1	$\square Q_3$	H_3	$\varnothing D$	A	C	Plenum box	m
	mm	mm	mm	mm	mm	mm	mm		kg
250	248	13	216	250	158	139	50	AK-Uni-008	2.7
300	298	13	266	250	158	139	50	AK-Uni-009	3.4
400	398	13	372	295	198	164	50	AK-Uni-002	5.8
500	498	13	476	345	248	189	48	AK-Uni-010	8.5
600	598	13	567	410	313	222	50	AK-Uni-011	11.6
625	623	13	567	410	313	222	50	AK-Uni-011	11.8

Weights apply to the supply air variant


Diffuser face ADLQ




ADLQ

Nominal size	Q_1 mm	Q_2 mm	A_{eff} m ²
250	248	198	0.0095
300	298	248	0.0175
400	398	348	0.0370
500	498	448	0.0675
600	598	548	0.1100
625	623	573	0.1230

Installation in T-bar ceilings, arrangement in a row



Installation in continuous ceilings




Installation and commissioning

- Preferably for rooms with a clear height up to 4.0 m
- Flush ceiling installation
- Horizontal or vertical duct connection
- If necessary, carry out volume flow rate balancing with the damper blade


These are only schematic diagrams to illustrate installation details.

Flush ceiling installation with square plenum box




- Horizontal duct connection
- Four suspension holes
- Suspension with cords, wires or hangers, to be provided by others

Diffuser face – sealing



- The self-adhesive sealing tape (supplied) has to be applied to the return edges of the plenum box by others


Diffuser face – central screw fixing



- Using the central fixing screw, fix the diffuser face to the cross bar of the plenum box
- Attach the decorative cap


Ceiling systems

Installation into grid ceilings




- Fix the plenum box to the ceiling
- The ceiling tile of the grid ceiling is independent of the ceiling diffuser
- Fix the diffuser face after the ceiling has been completed

Installation in continuous ceilings



- Fix plenum box (including diffuser face, if necessary) to the ceiling
- Adjust plasterboard ceiling tile as required
- If necessary, fix the diffuser face after the ceiling has been completed

Installation in T-bar ceilings



- Fix the plenum box to the ceiling
- The T-bar ceiling is independent of the ceiling diffuser
- Fix the diffuser face below the T-bars after the ceiling has been completed

Volume flow rate balancing

When several diffusers are connected to just one volume flow controller, it may be necessary to balance the volume flow rates.

- Ceiling diffusers with universal plenum box and damper blade (variant -M): The diffuser face can be removed to access the damper blade; the damper blade can then be set to any position between 0 and 90°
- Ceiling diffusers with universal plenum box, damper blade and pressure tap (variant -MN): The diffuser face need not be removed since the damper blade can be set with two cords (white and green).


Volume flow rate measurement

Ceiling diffusers with universal plenum box, damper blade and pressure tap (variant -MN) allow for volume flow rate balancing even with the diffuser face in place.

- Connect the measuring tube to the digital manometer
- Read the effective pressure
- Read the volume flow rate off the characteristic or calculate it
- If necessary, adjust the damper blade position with the cords


A characteristic is included with each AK-Uni plenum box.

AK-Uni-...-MN Volume flow rate balancing




Open, 0°

AK-Uni-...-MN Volume flow rate balancing



Closed, 90°

AK-Uni-...-MN volume flow rate measurement



Volume flow rate calculation for air density 1.2 kg/m³

$$\dot{V} = C \times \sqrt{\Delta p_w}$$

Volume flow rate calculation for other air densities

$$\dot{V} = C \times \sqrt{\Delta p_w} \times \sqrt{\frac{1.2}{\rho}}$$