


Ventilation grilles for installation into walls, sills or rectangular ducts

Type VAT



Ventilation grilles, made of aluminium, with individually adjustable, vertical blades

Ventilation grille with droplet shaped blades

- Nominal sizes 225 × 75 – 1225 × 525 mm
- Volume flow rate range 11 – 2000 l/s or 40 – 7200 m³/h
- Grille face made of aluminium with anodised finish
- Front border, 23 mm or 27 mm wide
- Concealed screw fixing

Optional equipment and accessories

- Grille face in RAL CLASSIC colours
- Installation subframe
- Installation subframe for fitting filter media
- Attachments for volume flow rate balancing and air direction control
- Spring clip fixing

Type		Page
VAT	General information	VAT – 2
	Function	VAT – 3
	Technical data	VAT – 6
	Quick sizing	VAT – 7
	Specification text	VAT – 8
	Order code	VAT – 9
	Dimensions and weight	VAT – 11
	Product details	VAT – 12
	Installation examples	VAT – 13
	Installation details	VAT – 14
	Commissioning	VAT – 15
	Basic information and nomenclature	VAT – 16

Application

Application

- Ventilation grille of Type VAT as supply air or extract air variant for comfort zones and industrial zones
- Directed supply air discharge for mixed flow ventilation
- Blades are adjustable to meet different local requirements
- For variable and constant volume flows
- For supply air to room air temperature differences from –12 to +4 K
- For installation in walls, sills and rectangular ducts

- Individually adjustable blades
- Front border in two widths
- Concealed screw fixing, spring clip fixing or countersunk holes
- Optional installation subframe and casing for the fitting of filter media

Nominal sizes

- Nominal length: 225, 325, 425, 525, 625, 825, 1025, 1225 mm
- Nominal height: 75, 125, 225, 325, 425, 525 mm

Other dimensions upon request

Special characteristics

Description

Variants

- Front border
- 27 mm wide
 - G11: 23 mm wide

Fixing

- Concealed screw fixing
- G11: Concealed screw fixing (23 mm)
- A11: Countersunk holes (only 27 mm)
- B11: Spring clip fixing (27 mm)
- H11: Spring clip fixing (23 mm)

Parts and characteristics

- Sloped border with chamfered inside edge
- Individually adjustable, vertical blades
- Factory fitted perimeter seal

Attachments

- AG, AS, D, DG: For volume flow rate balancing and for air direction control

Accessories

- Installation subframe: For the fast and simple installation of ventilation grilles

- Filter casing: Frame with filter element and spring clip fixing (only with 27 mm wide front border)

Construction features

- Asymmetrically supported blades

Materials and surfaces

- Border and blades made of aluminium
- Border and blades anodised, E6-C-0, natural colour
- P1: Border and blades powder-coated, RAL CLASSIC colour

Standards and guidelines

- Sound power level of the air-regenerated noise measured according to EN ISO 5135

Maintenance

- Maintenance-free as construction and materials are not subject to wear
- Inspection and cleaning to VDI 6022


Functional description

Ventilation grilles are air terminal devices for the supply air and extract air of ventilation and air conditioning systems. They direct the supply air into the room. Ventilation grilles with adjustable blades allow for adapting the discharge direction to the local conditions. The result is a mixed flow ventilation in comfort zones and industrial zones, with good overall room ventilation. Induction slows the airflow down, i.e. the airflow velocity decreases as the distance from the grille increases. The distance at which the airflow velocity reaches a certain defined value, e.g. 0.2 m/s, is called throw distance. The supply air jet from wall grilles that are installed near the ceiling


achieves a larger throw distance than a free jet (from a grille that is not installed near the ceiling). Single grilles, groups of grilles and continuous horizontal runs all achieve different throw distances.

In cooling mode it is necessary to take account of the jet deviation towards the occupied zone, which increases as the supply air to room air temperature difference increases and the discharge velocity decreases. In heating mode the supply air jet deviates towards the ceiling. This has no negative effect on the airflow velocity in the occupied zone, but it may affect the complete ventilation of the room.


Schematic illustration of a ventilation grille with transverse blades




Air pattern in cooling mode, with ceiling effect, sectional view




Air pattern in cooling mode, without ceiling effect, sectional view




Air pattern with ceiling effect, sectional view




Air pattern without ceiling effect, sectional view




Air pattern with ceiling effect, top view




Air pattern without ceiling effect, top view




Air pattern with ceiling effect, group of grilles, top view



Air pattern without ceiling effect, group of grilles, top view



Air pattern, group of grilles, top view



Several single grilles arranged in a row and with not much distance between them have the same effect as a continuous horizontal run.

Nominal sizes	225 × 75 to 1225 × 525 mm
Minimum volume flow rate	11 – 685 l/s or 40 – 2466 m³/h
Maximum volume flow rate, with L_{WA} max. 40 dB(A) without attachments	62 – 2000 l/s or 223 – 7200 m³/h
Supply air to room air temperature difference	–12 to +4 K

Volume flow rates apply to supply air

Geometric free area

H	L [mm]							
	225	325	425	525	625	825	1025	1225
mm	A_{geo} m²							
75	0.007	0.010	0.014	0.017	0.020	0.027	0.034	0.040
125	0.014	0.021	0.028	0.035	0.041	0.055	0.068	0.082
225	0.028	0.042	0.056	0.070	0.083	0.111	0.138	0.166
325		0.064	0.084	0.105	0.125	0.166	0.297	0.250
425					0.166	0.222	0.278	0.334
525							0.348	0.417

Effective air discharge area (supply air)

H	L [mm]							
	225	325	425	525	625	825	1025	1225
mm	A_{eff} m²							
75	0.007	0.011	0.014	0.018	0.021	0.029	0.036	0.043
125	0.014	0.021	0.029	0.036	0.043	0.057	0.072	0.086
225	0.029	0.043	0.057	0.072	0.086	0.114	0.142	0.172
325		0.064	0.086	0.108	0.129	0.172	0.214	0.256
425					0.172	0.228	0.285	0.342
525							0.355	0.427

Effective area of extract air grille

H	L [mm]							
	225	325	425	525	625	825	1025	1225
mm	A_{eff} m²							
75	0.006	0.009	0.011	0.014	0.016	0.022	0.028	0.033
125	0.011	0.016	0.022	0.028	0.033	0.044	0.055	0.066
225	0.022	0.033	0.044	0.055	0.066	0.090	0.110	0.134
325		0.050	0.066	0.083	0.100	0.134	0.170	0.200
425					0.134	0.180	0.220	0.270
525							0.280	0.340

This specification text describes the general properties of the product. Texts for variants can be generated with our Easy Product Finder design programme.

Ventilation grilles, rectangular, made of aluminium, for supply and extract air. Aesthetic sloped border with chamfered inside edge. Preferably for wall and sill installation but also suitable for rectangular ducts.

Ready-to-install component which consists of a border and individually adjustable, vertical blades. Concealed screw fixing, spring clip fixing or countersunk holes, for installation into an installation subframe or fixing onto an installation surface.

Sound power level of the air-regenerated noise measured according to EN ISO 5135.

Special characteristics

- Individually adjustable blades
- Front border in two widths
- Concealed screw fixing, spring clip fixing or countersunk holes
- Optional installation subframe and casing for the fitting of filter media

Materials and surfaces

- Border and blades made of aluminium

- Border and blades anodised, E6-C-0, natural colour
- P1: Border and blades powder-coated, RAL CLASSIC colour

Technical data

- Nominal sizes: 225 × 75 to 1225 × 525 mm
- Minimum volume flow rate (supply air):
11 – 685 l/s or 40 – 2466 m³/h
- Maximum volume flow rate (supply air), at L_{WA} max. 40 dB(A) without attachments:
62 – 2000 l/s or 223 – 7200 m³/h
- Supply air to room air temperature difference:
–12 to +4 K

Sizing data

– $\dot{V}$ _____
[m³/h]


– Δp_t _____
[Pa]

Air-regenerated noise


– L_{WA} _____
[dB(A)]

The weight table shows the available nominal sizes

VAT, 27 mm wide front border



VAT, 23 mm wide front border




VAT


H	L [mm]							
	225	325	425	525	625	825	1025	1225
mm	m							
	kg							
75	0.3	0.3	0.4	0.5	0.6	0.7	0.8	1.0
125	0.3	0.4	0.5	0.6	0.7	0.9	1.1	1.3
225	0.5	0.6	0.8	0.9	1.1	1.4	1.7	1.9
325		0.8	1.0	1.2	1.4	1.8	2.2	2.6
425					1.7	2.2	2.7	3.2
525							3.3	3.8

Weights apply to ventilation grilles without attachments


Front border, 27 mm



Front border B1
(23 mm)



Blade



Wall installation




Installation and commissioning


- Installation preferably in walls, sills and rectangular ducts
- Installation with installation subframe is recommended
- If no installation subframe is used, the border should be fixed with screws

These are only schematic diagrams to illustrate installation details.

Ventilation grille with concealed screw fixing



Ventilation grille with spring clip fixing



Volume flow rate balancing


When several ventilation grilles are installed on the same duct, it may be necessary to balance the volume flow rates.

- AG: Damper unit with opposed action blades, adjustable, secured with a locking screw
- AS: Damper unit with hit and miss damper, adjustable, secured with a locking screw

Air pattern


- Adjustable blades: Set the air control blades individually or together and depending on the local conditions
- D, DG: Air control blades, fitted at 90° to the front blades, can be adapted to the local conditions

Volume flow rate balancing -*G



Attachments -AG, -DG and Types AGW, DGW

Volume flow rate balancing -S



Attachments -AS, -KS, -RS and Type ASW